## **Forklift Seat Belt**

Seat Belt for Forklifts - Explained in the Regulation guidelines are the application of seatbelts and operator restraints on lift trucks. It says that the accountability falls on the employers' to make sure that every machine, piece of equipment and device is utilized correctly utilized in accordance to the instructions of the manufacturer.

Rough Terrain lift trucks have to meet the guidelines of ANSI Standard ASME B56.6-1992 regarding their use, design, maintenance, inspection and fabrication.

Mobile machines like for example side boom tractors along with a Rollover Protective Structure (ROPS), need to have seat belts that meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whatever mobile machine has seat belts required by law, the operator and subsequent passengers need to make certain they utilize the belts whenever the motor vehicle is in motion or engaged in operation because this can cause the machine to become unsteady and thus, unsafe.

If a seat belt or various operator restraint is needed on a forklift.

The seat belt requirements while working a lift truck depend on different factors. Whether the lift truck is equipped together with a Rollover Protective Structure, the type of forklift itself and the year the forklift was made all contribute to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 in the case of powered industrial trucks, is designed to assist the operator in lowering the chance of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device may consist of a seat belt, although a seat belt is not necessarily a part of such equipment or system.